



elison



elison

Ellison has produced a comprehensive technical and design support package which is available to architects and customers. We invite you to request any of the items including our technical binder with complete specifications and details and our interactive CD which fully explains our manufacturing processes, specs and details. An installation and maintenance CD is also available. Ask your representative about the hardware case which gives you an "up close" understanding of key Ellison balanced hardware components. In addition, complete specs and details are downloadable from our website.



Ellison Bronze, Inc.
125 West Main Street
Falconer, New York 14733
800-665-6445 Fax: 716-665-5552
www.ellisonbronze.com

BALANCED DOORS & CUSTOM ENTRANCE SOLUTIONS



ELLISON BALANCED DOORS



The balanced door concept, introduced by Ellison in 1928, provides opening and closing operation which is distinctly different from hinged, pivot hinged and continuous hinged door types. The door and frame are actually two parts of a proprietary component system which permits door operation with minimal opening pressure (or user effort), without the assistance of automatic and power-assisted operators.

When an Ellison Balanced Door is opened, approximately two thirds of the door swings outward while one third swings inward (at hinge" style), thus traveling on an elliptical arc rather than the circular path required by conventionally hinged doors, allowing external wind loads to help rather than hinder the user. The Ellison Balanced Door actually pivots on two arms - located at the top and bottom of the door - which are welded to a pivoting shaft located adjacent to the door. The shaft is connected in the frame header to a concealed hydraulic checking device, and is connected at the base to a geared floor box adjacent to the threshold. The shaft contains a torsion bar spring which provides the closing force for the door. The overhead hydraulic check is part of the "check and guide assembly" that both guides the door as it opens and provides adjustable, timed closing speed.

There are a number of benefits afforded by Ellison Balanced Doors. In addition to fingertip operation, which may eliminate the need for automatic and power assisted operators in many applications, the door system requires less interior and sidewalk space because of its elliptical path. Ellison Balanced Doors eliminate intrusive overhead boxes and hardware or cutouts in the floor, yet their rugged hydraulic checking units can be quickly and easily removed and replaced by maintenance staff.


POWER NOW

Patent Pending

PowerNow is a classic balanced door during manual operation, and opens with power only when needed. Our revolutionary design eliminates complicated, unsightly surface-mounted hardware. A concealed low energy operator and actuating arm provide opening force on demand. Our standard hardware provides the closing force. So, when used manually, PowerNow provides the same balanced door action you've come to expect from Ellison doors.

In the opening sequence below (viewed from the interior), note that the actuator arm is the only visible hardware. It pushes the door fully opened. After a timed delay, the door begins to close. The arm is fully independent of the door which is closing using the normal balanced door operation.

Power opens the door on demand, Ellison closes it.



Ellison PowerNow Doors are meeting high traffic challenges at Chicago's famed Field Museum where wheelchair accessibility and power operation must be combined with normal door use. PowerNow offers a trouble-free, dependable solution, because the patented design never engages the motor and actuator system during manual operation.







Formed stainless steel or bronze doors are constructed with a minimum stile width of 2-3/4" (3-1/2" preferred), a minimum top rail height of 2-3/4" (3-1/2" preferred), and a minimum bottom rail height of 6". Minimum face width of frame material is 3" in most cases, and frame depth is a minimum of 5". Glass and glass thickness may vary. Doors can be customized to suit the architect's concept.



FORMED STAINLESS STEEL AND BRONZE



FORMED STAINLESS STEEL AND BRONZE

PHYSICS AND ASTRONOMY BUILDING



FORMED STAINLESS STEEL AND BRONZE



Extruded aluminum doors and frames are similar in structural appearance to formed stainless or bronze doors. Aluminum extrusions are, of course, used in place of formed metal, and stiles are internally fastened to top and bottom rails during fabrication. Stile widths are available in 2-1/2", 3-1/2", and 4-1/2". Top rails are 2-1/2", 3-1/2", and 5". Bottom rail heights are 6", 7-1/2", 10" or greater with dress plates. Frames are 3"x 5" or 3"x 6". Glass thickness may vary. These doors can be customized. Offset aluminum frames, which present a dramatic sightline, are available.

FORMED STAINLESS STEEL AND BRONZE



EXTRUDED ALUMINUM



EXTRUDED ALUMINUM



Tempered glass doors are "all glass" doors which feature a top and bottom rail which secure the glass to the operating mechanism. Rails can be made in stainless steel, bronze or aluminum. Bronze and stainless rails are a minimum of 4-3/4" in height and standard aluminum are 4-3/4" and 10" in height. 1/2" tempered glass is used for doors up to 9'-0". 3/4" tempered glass is used for doors from 9'-0" to 10'-0". Narrow stile doors are essentially the same as tempered glass doors but feature thin, decorative stile edges. The stiles can be made from clad bronze or stainless steel, or from extruded aluminum. 1/2" tempered glass is used for doors up to 10'-0". Consult factory for taller applications.

TEMPERED GLASS & NARROW STILE



TEMPERED GLASS & NARROW STILE




Virtually every Ellison Door is a custom door. Ellison has been very successful in meeting unique and unusual architectural requirements which extend beyond Ellison's primary specification. As examples, doors can be made up to 10'-0" or higher in certain applications, and wood doors can be fitted with balanced hardware. Panel doors, flush doors, custom vision lites, unique embellishments, special glass moldings, finishes and exotic metal combinations are all available to the designer. Door operation can be other than balanced including sliders, rolling doors, center pivoted, hinged and curved doors. Ellison has a time honored tradition of working closely with architects to help engineer and fabricate these special requests.

SPECIALTY



Ellison Balanced Wood Doors are distinctly different from conventional doors. When an Ellison Balanced Door opens, 2/3 of the door swings outward while 1/3 swings inward, thus traveling on an elliptical arc rather than the circular path required by hinged doors. This unique opening motion allows external wind loads to help, rather than hinder, the user. The Ellison Door actually pivots on two arms – located at the top and bottom of the door – which are welded to a pivoting shaft adjacent to the door. The shaft is connected in the frame header to a concealed hydraulic checking device, and is connected at the base to a geared floor box adjacent to the threshold. The shaft contains a torsion bar spring which provides the closing force for the door. The overhead hydraulic check and guide assembly guides the door as it opens and provides adjustable, timed closing speeds.



PROJECT CREDITS



Cover
1111 Broadway
Oakland, California



Page 2
Imperial Bank Tower
Costa Mesa, California
Architect: Murphy / Jahn



Page 3
Corning Incorporated
Corning, New York
Architect: Kevin Roche,
John Dinkeloo and
Associates



Page 12
Electronics For Imaging, San Francisco, California
Architect: Gensler & Associates



Page 12
Fairmont Hotel Tower
San Jose, California
Architect:



Page 12
Allerton Hotel
Chicago, Illinois
Architect: Eckenhoff
Saunders



Page 5
Museum
Chicago, Illinois



Page 6
Vodak-Eastside
Branch Library
Chicago, Illinois
Architect: MEC/SMLA
Joint Venture



Page 6
Logan Square
Branch Library
Chicago, Illinois
Architect: Guajardo
Associates Ltd.



Page 12
650 California Street, San Francisco, California
Architect: Karl T. Korth / James Sunseri Architects



Page 13
ULCA Physics
& Astronomy Building
Los Angeles, California
Architect: Anshen
& Allen



Page 14
Santa Monica
Public Safety Facility
Santa Monica, California
Architect: Dworsky
& Associates



Page 6
USC Ronald Tutor Hall
Los Angeles, California
Architect: A.C. Martin
Partners, Inc.



Page 6
USC Ronald Tutor Hall
Los Angeles, California
Architect: A.C. Martin
Partners, Inc.




Page 6
The California Endowment Headquarters
Los Angeles, California
Architect: House & Robertson Architects



Page 14
Monterey Bay Aquarium
Monterey, California
Architect: Esherick,
Homsey, Dodge & Davis



Page 14
Jones Theatre
Denver, Colorado
Architect: Roche
Dinkeloo & Associates



Page 14
Chicago Branch Library
Chicago, Illinois
Architect: Guajardo
Associates



Page 7
USC Ronald Tutor Hall
Los Angeles, California
Architect: A.C. Martin
Partners, Inc.



Page 8
67 Wall Street
New York, New York
Architect: Haffey Architects
& Engineers




Page 8
Experian Corporate
Headquarters
Costa Mesa, California
Architect: Johnson,
Fain & Partners



Page 14
Electronic Arts
Redwood City, California
Architect: Skidmore,
Owings & Merrill



Page 14
2nd & Josephine
Denver, Colorado
Architect: River Studio
Architects




Page 15
Monterey Bay Aquarium
Monterey, California
Architect: Esherick,
Homsey, Dodge & Davis



Page 8
16 Market Square
Denver, Colorado
Architect: Quinlivan,
Pierik & Krause



Page 8
345 California Street
San Francisco, California
Architect: Skidmore,
Owings & Merrill



Page 8
Crown Hall, Illinois Institute of Technology
Chicago, Illinois
Architect: Ludwig Mies van der Rohe



Page 16
Oriole Park Branch Library, Chicago, Illinois
Architect: Jackson Architects, LLC




Page 16
Foster City Government Center
Foster City, California
Architect: Des Architects and Engineers




Page 16
Foster City
Government Center
Foster City, California
Architect: Des Architects
and Engineers



Page 9
Experian Corporate
Headquarters
Costa Mesa, California
Architect: Johnson,
Fain & Partners



Page 10
1111 Broadway, Oakland, California



Page 10
Adobe Tower, San Francisco, California
Architect: Hellmuth, Obata & Kassabaum




Page 16
Stickney Forest View
Public Library
Stickney, Illinois
Architect: Frye, Gillan,
Molinario Architects




Page 17
Rossmoor
Walnut Creek, California
Architect: Architectural
Dimensions



Page 18
Japanese American National Museum
Los Angeles, California
Architect: Hellmuth, Obata & Kassabaum



Page 10
Shearson Lehman Plaza
New York, New York
Architect:
Kohn Pedersen Fox
Associates, P.C.



Page 10
Saks Fifth Avenue
Santa Barbara,
California
Architect: Ceernal
Architects, Inc.




Page 11
1111 Broadway
Oakland, California



Page 18
Rogers Park Branch Library, Chicago, Illinois
Architect: Antunovich Associates, Inc.



Page 18
Valentino Boutique
New York, New York
Architect: Peter Marino
Architect



Page 18
Wildlife Experience
Denver Colorado
Architect: Klipp, Colussy,
Jenks, Dubois



Page 19
One America Plaza
San Diego, California
Architect: Murphy / Jahn




Page 20
Milwaukee Art Museum, Milwaukee, Wisconsin
Architect: Kahler Slater Associates



Page 20
Ameritech Office Center, Hoffman Estates, Illinois
Architect: Lohan Associates



Page 20
Art Institute of Chicago
Chicago, Illinois
Architect: Gilmore Franzen Architects



Page 20
First National Bank
San Diego, California
Architect: Keating, Mann, Jernigan & Rottet



Page 21
Giorgio Armani
New York, New York
Architect: Peter Marino Architect




Page 22
Saks, Cherry Creek Mall, Denver, Colorado
Architect: Robert J. Bridges



Page 22
The Gas Company Tower, Los Angeles, California
Architect: Skidmore, Owings & Merrill



Page 22
300 East Randolph
Chicago, Illinois
Architect: Lohan Associates



Page 22
Mt. Sinai Hospital
New York, New York
Architect: Pei, Cobb, Freed & Partners Architects



Page 23
Santa Ana Police Administration & Holding Facility
Santa Ana, California
Architect: Hellmuth, Obata & Kassabaum



Page 24
Ronald Reagan Building, Washington, D.C.
Architect: PEI, Cobb, Freed & Partners



Page 24
65 East Goethe, Chicago, Illinois
Architect: Lucien LaGrange Architects
Grillework: Antares Iron & Copper Work Shop



Page 24
Lake Forest Graduate School of Management
Chicago, Illinois
Architect: The Davis Adams Group, Ltd.



Page 24
Chicago Sinai Congregation, Sinai Temple
Chicago, Illinois
Architect: Lohan Associates



Page 25
136 Madison Avenue
New York, New York
Architect: S.P. Papadatos Associates P.C.
Grillework: LMC Corporation



Page 26
Metra North Glenview Station
Glenview, Illinois
Architect: Frega Associates



Page 27
Metra North Glenview Station
Glenview, Illinois
Architect: Frega Associates

We Think Every Great Door Should Have A Dependable Warranty.*
How's Ten Years?

From Ellison Bronze. Don't Argue.
*We cover the entire door, frame and closing hardware.

ellison
For additional information, technical literature and sales, write, fax or call:
Ellison Bronze, A Division of Downcraft Corporation
125 West Main Street / Fishkill, New York 12521 / 716-665-6522 / Fax: 716-665-5552

Several years ago, we inaugurated a new warranty program which was unique in the custom door industry. Instead of limiting our warranty to one part of the door or another, we warrant the entire product manufactured in our plant. This is a plain English agreement reprinted here unedited: Ellison Bronze warrants materials used in its doors, frames and closing hardware, and the fabrication of the above items against defect in material or workmanship for a period of ten years from the date of acceptance of the completed Ellison product. During the ten year period of warranty Ellison agrees to repair, correct or replace any defective material or workmanship within reasonable time after receipt of written notice of such defect from the architect, owner or buyer. All labor to replace warranted parts is by others. This warranty does not cover the surface discoloration of copper alloy sheets or extrusions, the breakdown of protective coatings when furnished to the architect's specification and applied as directed, or to adjustments made necessary by the shifting or settling of the building structure. This warranty does not apply to door pull locks or other hardware not originally manufactured by Ellison. All finished hardware and material not fabricated by Ellison is to carry the manufacturers standard warranty.